

# MATERIAL AND SAFETY DATA SHEET

## Powder Free Chlorinated Latex Examination Gloves

### Factory:

**Supermax Glove Manufacturing Sdn Bhd**

Lot 38, Putra Industrial Park

Bukit Rahman Putra

47000 Sungai Buloh

Selangor DE

Malaysia

Tel: (603) 61452328

Fax: (603) 61562191

### SECTION 1

### COMPOSITION

These gloves are made of 100% Natural Rubber Latex providing strength, comfort, superior fit and grip due to its elastic properties.

### SECTION 2

### PHYSICAL DATA

Meet with the requirements of ASTM D3578:2005 Standard Specification for Rubber Examination Gloves and BS EN455-1, 2 and 3:2000 Medical Gloves for Single Use.

Width	95 ± 10 mm (size medium)
Length	240 mm minimum
Thickness	0.08 mm minimum (providing tactile sensitivity)
Tensile Strength (unaged)	18.0 MPa minimum (providing superior strength)
Ultimate elongation (unaged)	6500% minimum
Tensile Strength (aged)	14.0 MPa minimum
Ultimate elongation (unaged)	500% minimum
Watertightness	Substantially impermeable to water vapour and liquid water providing an excellent biological barrier. Double gloving is recommended for reduced risk.

### SECTION 3 HEALTH HAZARD INFORMATION

Biocompatibility data

Guinea Pig Sensitization (Buehler) -  
Did not indicate a potential for dermal irritation or allergic contact sensitization.

Repeated Insult Patch Test -  
Did not indicate a potential for dermal irritation or allergic contact sensitization.

### SECTION 4 FIRST AID MEASURES

Skin

Warning: Isolated cases of allergic reactions to latex rubber have been reported. If you experience a reaction to this product, discontinue use immediately and seek for medical help. This product contains Natural Rubber Latex which may cause allergic reactions in some individuals.

Other components used in making gloves may also cause allergic reactions in some users.

**Note: Leaching and washing processes undertaken during the manufacture of powder free gloves have significantly reduced protein level and residual chemical levels in gloves.**

### SECTION 5 HANDLING AND STORAGE

Storage

Store in cool, dry place, avoid excessive heat (40 ° C, 104 ° F). Open box should be shielded from exposure to direct sun or fluorescent lighting.

Disposal

Material may be recycled or disposed of in accordance to local disposal regulations.

Fire Hazard

Flammable. Suitable extinguishing media are: - dry extinguishing media, foam.

## **SECTION 6                    SPECIAL PROTECTION INFORMATION**

In accordance to EN 374-3: 1994 Permeation by Chemicals

40% Sodium hydroxide	Class 4
40% Sulphuric acid	Class 6